

FLAME RETARDANT FOAM

Product Name	Density (Kg/m ³)	Hardness (25% ILD) (kg./314 cm ²)	Color	Standard Size (mm)	Test Method
UED-20	20.0 ± 2.0	10.0 ± 2.0	Black	2000 x 1000	FMVSS 302
UEK-1	24.0 ± 2.0	10.0 ± 2.0	Grey	2000 x 1000	FMVSS 302
UEK-30	30.0 ± 2.0	10.0 ± 2.0	Black	2000 x 1100	FMVSS 302
UFL-30	30.0 ± 2.0	10.0 ± 2.0	Grey	1550 x 1000	FMVSS 302
UFL-50	50.0 ± 3.0	22.0 ± 3.0	White	1550 x 2000	FMVSS 302
UEI-3	20.0 ± 2.0	9.0 ± 2.0	Grey	2000 x 1000	FMVSS 302
F-2	25.0 ± 3.0	13.0 ± 2.0	Black	2000 x 1000	FMVSS 302
UEA-4	39.0 ± 3.0	12.0 ± 2.0	Cream	2030 x 1270	CAL 117-2013
UEA-5	34.0 ± 2.0	8.0 ± 2.0	Blue	2030 x 1270	CAL 117-2013
UEA-6	26.0 ± 3.0	16.0 ± 2.0	White	2030 x 1270	CAL 117-2013
UEA-8	39.0 ± 3.0	16.0 ± 2.0	Grey	2030 x 1270	CAL 117-2013
UEA-28	28.0 ± 3.0	16.5 ± 3.0	Yellow	1930 x 1750	CAL 117-2013
UEI-3	20.0 ± 2.0	9.0 ± 2.0	Grey	2000 x 1000	UL-94 HF-1
F-2	25.0 ± 2.0	13.0 ± 2.0	Black	2000 x 1000	UL-94 HF-1
UFL-30	30.0 ± 2.0	12.0 ± 2.0	White	2000 x 2000	BS 5852 Part 1